

S.N.	Equipment & Specifications	Qty
1.	<p><u>15-Inch Double Speaker</u></p> <ul style="list-style-type: none"> • Speaker Size : Dual 15 -inch woofers with high -power sound output. • Power Handling : Approx. 2000W peak power (model dependent). • Frequency Response : Around 45Hz-20Hz for bass and clear audio. • Impedance : Usually 4Ω or 8 Ω for amplifier compatibility. • Features : Strong bass, durable cabinet, and suitable for DJ or PA use. 	1 Set
2	<p><u>12" Monitor Speaker :</u></p> <ul style="list-style-type: none"> • Power Rating: 100W RMS / 200W Program • Speaker Type: 12-inch (30.48 cm) Full Range Dual Cone + Piezo Horn Tweeter • Frequency Response: 55Hz – 20,000Hz • Impedance: 8Ω, 2-Way Monitor Speaker Design • Cabinet: Bass Reflex, carpet-covered enclosure, approx. 16.2 kg weight 	1 SET
3	<p><u>Music Keyboard Specifications</u></p> <ul style="list-style-type: none"> • Keys: 61 full-size, velocity-sensitive keys (touch response). • Polyphony & Sounds: 128-note polyphony, 391 tones + 256 GM2 tones, 9 drum kits. • Rhythms & Songs: 253 accompaniment styles, 140 built-in songs, records up to 10 songs. • Speakers & Power: Built-in 3W + 3W speakers (10 cm × 2), AC adaptor or AA battery operation. • Connectivity & Size: USB-B, headphone/output jacks, sustain pedal input; approx. 956 × 360 × 133 mm, 5 kg. 	1
4	<p><u>Mixer</u></p> <ul style="list-style-type: none"> • Channels: 16-channel mixer (10 Mic / 16 Line inputs, 8 mono + 4 stereo). • Effects: Built-in SPX digital effects with 24 preset effects and D-PRE microphone preamps. • USB Audio: 2-in / 2-out USB interface, 24-bit / 192kHz recording quality. • Output & Features: 4 AUX sends, 4 GROUP buses, +48V phantom power, one-knob compressors (Ch 1–8). 	1

	<ul style="list-style-type: none"> Size & Weight: Approx. 444 × 130 × 500 mm, weight 6.8 kg, rugged metal chassis 	
5	<p><u>Speaker</u></p> <ul style="list-style-type: none"> Speaker Type: 15-inch 2-way speaker. Power Output: 1000W peak, Inputs: Spoken Jack Size & Weight: Approx. 707 × 439 × 365 mm, 22 KG 	1 SET
6	<p><u>Monitor Amplifier</u></p> <ul style="list-style-type: none"> Power Output: 100W – 500W RMS (depends on model). Frequency Response: 20Hz – 20kHz for clear audio reproduction. Impedance: Supports 4Ω / 8Ω speaker load. Inputs & Outputs: XLR, RCA or 6.35mm input with speaker output terminals. Features: Low distortion, cooling fan, overload protection, and volume control. 	1

